

SF5S4

40V 5A


FEATURES

- Tj150°C
- P_{R_{RSM}} avalanche guaranteed
- Fully Isolated Molding
- Dielectric strength 1.5KV guaranteed

APPLICATION

- Switching power supply
- DC/DC converter
- Home Appliances, Office Equipment
- Telecommunication

OUTLINE DIMENSIONS



RATINGS

- Absolute Maximum Ratings (If not specified T = 25°C)


Item	Symbol	Conditions	Ratings	Unit
Storage Temperature	Tstg		-40~150	°C
Operating Junction Temperature	Tj		150	°C
Maximum Reverse Voltage	V _{RM}		40	V
Repetitive Peak Surge Reverse Voltage	V _{RRSM}	Pulse width 0.5ms, duty1/40	45	V
Average Rectified Forward Current	I _O	50Hz sine wave, R-load, Tc=136°C	5	A
Peak Surge Forward Current	I _{FSM}	50Hz sine wave, Non-repetitive 1 cycle peak value, Tj=25°C	150	A
Repetitive Peak Surge Reverse Power	P _{RRSM}	Pulse width 10 μs, Tj=25°C	330	W
Dielectric Strength	V _{dis}	Terminals to case, AC 1 minute	1.5	kV
Mounting Torque	TOR	(Recommended torque 0.3N·m)	0.5	N·m

- Electrical Characteristics (If not specified T ≒25℃)

Item	Symbol	Conditions	Ratings	Unit
Forward Voltage	V_F	$I_F=5A$, Pulse measurement	Max.0.55	V
Reverse Current	I_R	$V_R=V_{RM}$, Pulse measurement	Max. 3.5	mA
Junction Capacitance	C_j	$f=1MHz$, $V_R=10V$	Typ.180	pF
Thermal Resistance	θ_{jc}	junction to case	Max.3.5	°C/W


SF5S4

Forward Voltage




SF5S4

Junction Capacitance




SF5S4

Reverse Current




SF5S4

Reverse Power Dissipation




$T_j = 150^\circ\text{C}$




SF5S4

Forward Power Dissipation




$T_j = 150^\circ\text{C}$




SF5S4

Derating Curve




$V_R = 20\text{V}$



SF5S4

Peak Surge Forward Capability



SBD Repetitive Surge Reverse Power Derating Curve

